

1 Identification of the substance/preparation and of the company/undertaking

· **Product details**

· **Trade name:** *Signierspray 500 ml*

· **Application of the substance / the preparation** *Paint*

· **Manufacturer/Supplier:**

Lyra-Bleistift Fabrik GmbH&Co.KG

Willstätterstr. 54-56

90449 Nürnberg

· **Further information obtainable from:** *Abteilung Produktsicherheit*

· **Information in case of emergency:**

Beratungsstelle für Vergiftungserscheinungen und Embryonaltoxikologie, Berlin Tel.: 0049 / 030 / 19240

2 Hazards identification

· **Hazard description:**



F+ Extremely flammable

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

R 12 Extremely flammable.

R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 67 Vapours may cause drowsiness and dizziness.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

73.4 % by mass of the contents are flammable

Keep out of the reach of children

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **GHS label elements**



Danger

2.3/1 - Extremely flammable aerosol.



Warning

3.8/3 - May cause drowsiness or dizziness.

4.1/3 - Harmful to aquatic life with long lasting effects.

· **Prevention:**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

Printing date 12.05.2009

Revision: 11.05.2009

Trade name: Tignierspray 500 ml

'Contd. of page 1x

- Response:
IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
Call a POISON CENTER or doctor/physician if you feel unwell.
- Torage:
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Protect from sunlight. Do no expose to temperatures exceeding 50°C/ 122°F.
- Disposal:
Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

- Chemical characterization
- Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 106-97-8 EINECS: 203-448-7	butane F+; R 12 Danger: 2.2/1 Warning: 2.5/L	25-50%
CAS: 74-98-6 EINECS: 200-827-9	propane F+; R 12 Danger: 2.2/1 Warning: 2.5/L	10-25%
CAS: 64742-49-0 EINECS: 265-151-9	Naphtha (petroleum), hydrotreated light Xn, Xi, F, N; R 11-38-51/53-65-67 Danger: 2.6/2; 3.10/1 Warning: 3.2/2, 3.8/3 4.1.C/2	10-25%
CAS: 67-64-1 EINECS: 200-662-2	acetone Xi, F; R 11-36-66-67 Danger: 2.6/2 Warning: 3.3/2A, 3.8/3	10-25%
CAS: 141-78-6 EINECS: 205-500-4	ethyl acetate Xi, F; R 11-36-66-67 Danger: 2.6/2 Warning: 3.3/2A, 3.8/3	2.5-10%

· Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

5 Fire-fighting measures

- Tuitable extinguishing agents: CO₂, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet

'Contd. on page 3x



Printing date 12.05.2009

Revision: 11.05.2009

Trade name: Tignierspray 500 ml

'Contd. of page 2x

· Protective equipment: No special measures required.

6 Accidental release measures

- Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- Measures for environmental protection:
 - Do not allow product to reach sewage system or any water course.
 - Inform respective authorities in case of seepage into water course or sewage system.
 - Do not allow to enter sewers/ surface or ground water.
- Measures for cleaning/collecting:
 - Ensure adequate ventilation.
 - Do not flush with water or aqueous cleansing agents

7 Handling and storage

- Handling:
 - Information for safe handling:
 - Ensure good ventilation/exhaustion at the workplace.
 - Open and handle receptacle with care.
 - Information about fire - and explosion protection:
 - Do not spray onto a naked flame or any incandescent material.
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
 - Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- Storage:
 - Requirements to be met by storerooms and receptacles:
 - Store in a cool location.
 - Observe official regulations on storing packagings with pressurized containers.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions:
 - Keep container tightly sealed.
 - Do not seal receptacle gas tight.
 - Store in cool, dry conditions in well sealed receptacles.
 - Protect from heat and direct sunlight.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane

WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

67-64-1 acetone

WEL	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
-----	--

141-78-6 ethyl acetate

WEL	Short-term value: 400 ppm Long-term value: 200 ppm
-----	---

'Contd. on page 2x



Printing date 12.05.2009

Revision: 11.05.2009

Trade name: Signierspray 500 ml

(Contd. of page 3)

- **Additional information:** *The lists valid during the making were used as basis.*
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
- **Respiratory protection:**
*In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Use suitable respiratory protective device in case of insufficient ventilation.*
- **Protection of hands:**



Protective gloves

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· General Information

Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: -44°C

· **Flash point:** < 0°C

· **Ignition temperature:** 365°C

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower:	0.7 Vol %
Upper:	13.0 Vol %

· **Vapour pressure at 20°C:** ~ 4200 hPa

· **Density at 20°C:** 0.84 g/cm³

(Contd. on page 5)



Printing date 12.05.2009

Revision: 11.05.2009

Trade name: Signierspray 500 ml

(Contd. of page 4)

· **Solubility in / Miscibility with water:** Partly miscible.

· **Solvent content:**
Organic solvents: 86.76 %
VOC (EC) 86.76 %
87.70 %

· **Solids content:** 13.24 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**
- **Primary irritant effect:**
 - **on the skin:** No irritant effect.
 - **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

12 Ecological information

- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms

13 Disposal considerations

- **Product:**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**
08 02 99 | wastes not otherwise specified

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

GB

(Contd. on page 6)

Printing date 12.05.2009

Revision: 11.05.2009

Trade name: Signierspray 500 ml

(Contd. of page 5)

14 Transport information

· Land transport ADR/RID (cross-border)



- **ADR/RID class:** 2 5F Gases.
- **Danger code (Kemler):** -
- **UN-Number:** 1950
- **Packaging group:** -
- **Hazard label:** 2.1
- **Description of goods:** 1950 AEROSOLS

· Maritime transport IMDG:



- **IMDG Class:** 2.1
- **UN Number:** 1950
- **Label:** 2.1
- **Packaging group:** -
- **EMS Number:** F-D,S-U
- **Marine pollutant:** No
- **Proper shipping name:** AEROSOLS

· Air transport ICAO-TI and IATA-DGR:



- **ICAO/IATA Class:** 2.1
- **UN/ID Number:** 1950
- **Label:** 2.1
- **Packaging group:** -
- **Proper shipping name:** AEROSOLS, flammable

- **UN "Model Regulation":** UN1950, AEROSOLS, 2.1

15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:

F+ Extremely flammable

· Risk phrases:

12 Extremely flammable.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

67 Vapours may cause drowsiness and dizziness.

(Contd. on page 7)



LYRA

SCHEDA DI SICUREZZA

secondo 1907/2009/EC, articolo 31

Printing date 12.05.2009

Revision: 11.05.2009

Trade name: Signierspray 500 ml

(Contd. of page 6)

· **Safety phrases:**

- 2 Keep out of the reach of children.
- 3 Keep in a cool place.
- 23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
- 24 Avoid contact with skin.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 33 Take precautionary measures against static discharges.
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 46 If swallowed, seek medical advice immediately and show this container or label.

· **Special labelling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
73.4 % by mass of the contents are flammable
Keep out of the reach of children

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

- 11 Highly flammable.
- 12 Extremely flammable.
- 36 Irritating to eyes.
- 38 Irritating to skin.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement internationale concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
VOC: Volatile Organic Compounds (USA, EU)

GB



F.lli AMOS & C. S.p.A.

Viale Europa 68/70, I-20093 COLOGNO MONZESE (MI) - ITALIA
Tel. 02 251111.1 - Telefax 02 2538379 - www.amos.it - e-mail: amos@amos.it

COLOGNO M. • PADOVA • BOLOGNA • NAPOLI